

High Power 2 μm DPSSL Modules

- . Compact monolithic laser systems
- . Highly efficient diode pumping
- . Fiber-coupled versions available
- . No high-voltage required
- . Reduced waste heat
- . Maintenance free
- . Process variability



Specifications

	DPM-25 (Tm:YAG) free / fiber ⁽¹⁾	DPM-50 (Tm:YAG) free / fiber ⁽¹⁾	DPM-100 (Tm:YAG) free / fiber ⁽¹⁾
Optical Parameters			
. Wavelength	2020 nm	2020 nm	2020 nm
. Average Output Power (max)	25 / 20 W	50 / 40 W	100 / 80 W
. Pulse Energy (max)	(0.2 - 1.6 ⁽²⁾) / (0.16 - 1,28 ⁽²⁾) J	(0.5 - 4 ⁽²⁾) / (0.4 - 3.2 ⁽²⁾) J	(1 - 8 ⁽²⁾) / (0.8 - 6.4 ⁽²⁾) J
. Pulse Repetition Rate (max)	500 Hz	500 Hz	500 Hz
. Pulse Duration	100 to 500 (20 000 ⁽²⁾) μs	100 to 500 (20 000 ⁽²⁾) μs	100 to 500 (20 000 ⁽²⁾) μs
. Average Current (max)	8 A	7 A	7 A
. Mode of Operation	Pulsed	Pulsed	Pulsed
. Efficiency (optical-optical)	> 15 %	> 20 %	> 20 %
. Beam Shape (focus)	top hat like	top hat like	top hat like
. Free Beam Quality	$M^2 < 20$	$M^2 < 30$	$M^2 < 40$
. Free Beam Diameter	1.6 mm	1.6 mm	1.6 mm
. Free Divergence (half angle)	< 20 mrad	< 30 mrad	< 40 mrad
. Fiber Diameter Low-OH ⁽¹⁾	$\sim 100 \mu\text{m}$ (NA < 0.2)	$\sim 150 \mu\text{m}$ (NA < 0.2)	$\sim 200 \mu\text{m}$ (NA < 0.2)
Cooling Requirements			
. Coolant	Distilled water with Algaecide and Corrosion Inhibitor	Distilled water with Algaecide and Corrosion Inhibitor	Distilled water with Algaecide and Corrosion Inhibitor
. Coolant Temperature	25 °C	25 °C	25 °C
. Coolant Flow Rate	> 4 lpm	≥ 5 lpm	≥ 6 lpm
. Coolant Pressure	(2 - 5) bar	(3 - 5) bar	(3 - 5) bar
. Required Cooling Power	≥ 350 W @ 25 °C Environment Temperature	≥ 500 W @ 25 °C Environment Temperature	≥ 750 W @ 25 °C Environment Temperature
Electrical Parameters			
. Diode Forward Voltage	< 40 V	< 75 V	< 130 V
. Diode Forward Current	150 A	150 A	150 A
. Average Power Consumption (max)	< 500 W	< 750 W	< 1000 W
Mechanical Dimensions			
. W x D x H	120 x 96 x 75 mm	120 x 96 x 75 mm	120 x 120 x 75 mm
. Weight	1.5 kg	1.6 kg	1.7 kg
. Emission Height	47.5 mm	47.5 mm	47.5 mm


⁽¹⁾ Fiber as specified by Pantec

⁽²⁾ With Pantec Ultrapulse Mode (on request only)

Laser Diode Drivers

The LDD series are economic QCW laser diode driver modules designed to provide high current pulses to drive 3m.i.k.r.o.n.[™] modules in various applications. It delivers output currents up to 150 A and pulse widths variable from 50 up to 500 μ s operation. Up to 1000 W average output power is available with the supplied heatsink and forced air flow. Several safety features are integrated to protect both laser diode and driver.

	DPM-25 (Tm:YAG)	DPM-50/100 (Tm:YAG)
Laser Diode Driver	LDD-36200	LDD-120200
• Output Current	up to 150 A	up to 150 A
• Rise Time (10 - 90%)	< 20 μ s	< 20 μ s
• Efficiency	> 80 %	> 80 %
• Mechanical Dimensions (W x D x H)	200 x 150 x 85 mm	300 x 200 x 120 mm



Test and Evaluate



The 3m.i.k.r.o.n.[™] evaluation kits are ready-to-use and straightforward laboratory systems for first feasibility studies in research environment. The evaluation kits are available with two different kind of laser sources (see front page), shortens the development time, enables flexibility and a fast demonstration of feasibility. The test systems are delivered with your requested laser source, a laser control system and a cooling system for laboratory use only.

Please contact us for more information on rental or purchase conditions: 3um@pantec.com

3m.i.k.r.o.n.[™] Applications

Medical	Industrial
<ul style="list-style-type: none"> • Aesthetics / Dermatology • Dentistry • ENT • Lithotripsy • Minimally-Invasive Surgery • Orthopedics • etc. 	<ul style="list-style-type: none"> • Material Processing (Drilling, Cutting, Melting, Welding, Evaporation) • Analytics • Security • Defense

More Services



Customized laser sources
Optical and mechanical design
Contract development and manufacturing
Medical device consulting (IP research, Medical CE, ...)

