


# High Power Laser Diode Driver

**3mikron**<sup>TM</sup>  
Innovative Laser Systems

- . 300 A pulsed output current
- . (50 to 1000)  $\mu$ s pulse width
- .  $\geq 80\%$  efficiency
- . Protective features
- . Auto adjust of output voltage



## Specifications

	LDD-20300	LDD-30300	LDD-38200	LDD-140300
Electrical Parameters				
. Output Voltage (self adaptable)	(2 - 20) V	(8 - 30) V	(10 - 38) V	(60 - 140) V
. Output Current (max)	300 A	300 A	200 A	300 A
. Supply Voltage	24 - 28 V	48 V	24 - 28 V	48 V
. Input Power (max)	720 W	1200 W	720 W	1200 W
. Rise Time (10 - 90 %)	$\leq 20 \mu$ s	$\leq 20 \mu$ s	$\leq 20 \mu$ s	$\leq 20 \mu$ s
. Maximum Average Output Current	25 A	25 A	7.5 A	7.5 A
. Pulse Width	50 $\mu$ s - 1 ms <sup>(1)</sup>	50 $\mu$ s - 1 ms <sup>(1)</sup>	(50 - 500) $\mu$ s	(50 - 500) $\mu$ s
. Maximum Operating Frequency	2 kHz	2 kHz	2 kHz	2 kHz
. Interfaces	Interlock, Current monitor, Trigger in, Trigger out, Laser enable, CAN, RS232, USB, Relay output			

<sup>(1)</sup> 600  $\mu$ s standard, 1 ms on request

The LDD is an economic QCW laser diode driver module designed to provide high current pulses to drive 2m.i.k.r.o.n.<sup>TM</sup> and 3m.i.k.r.o.n.<sup>TM</sup> modules in various applications. It delivers output currents up to 300 A and pulse widths variable from 50 up to 1000<sup>(1)</sup>  $\mu$ s operation. Several safety features are integrated to protect both laser diode and driver.



Pantec Biosolutions AG

Industriering 21 · 9491 Ruggell · Liechtenstein

Tel: +423 377 13 33 · Fax: +423 377 13 34

info@pantec-biosolutions.com www.pantec-biosolutions.com

Illustrations, descriptions and technical data are not binding and may be changed without notice.  
Copyright Pantec Biosolutions AG, Ruggell, Liechtenstein, 2023 - All rights reserved.

**pantec**

# Ultra Compact Tapered Laser Diode Driver

single frequency  
Tapered Laser Diodes

- . 2 x 12.5 A output current (50 µs - CW)
- . 4 x 750 mA (CW)
- . > 80% efficiency
- . Protective features
- . Auto adjust of output voltage



## Specifications

bdd-0312-CW

### Electrical Parameters

. Output Voltage (self adaptable)	1 - 3 V
. Output Current (max)	2 x 12.5 A (50 µs - CW) and 4 x 750 mA (CW)
. Supply Voltage	12 V
. Input Power (max)	100 W
. Rise Time (10 - 90 %)	≤ 50 µs
. Pulse Width	50 µs - CW
. Maximum Operating Frequency	50 kHz
. Cooling	Forced air
. Interfaces	Interlock, Current monitor, Trigger in, Trigger out, Laser enable, UART, USB, Fan

The TLDD is an economic pulsed and CW laser diode driver module designed to provide high current pulses to drive fam™ modules in various applications. It delivers output currents of 2 x 12.5 A and 4 x 750 mA and pulse widths variable from 50 µs to CW operation. Several safety features are integrated to protect both laser diode and driver.

